

FOR THOSE WHO DEMAND MORE. JX STRADDLE SERIES

CASE II
AGRICULTURE



MODELS	JX 60	JX 70	JX 80	JX 90	JX 95
ENGINE	8035.05D.939	8035.25C.939	8045.05R.939	8045.25.939	8045.25-L939
No. of cylinders / aspiration	3 / Natural	3 / TC	4 / Natural	4 / TC	4 / TC
Capacity / Bore x stroke(cm ³) / (mm)	2931 / 104 x 115	2931 / 104 x 115	3908 / 104 x 115	3908 / 104 x 115	3908 / 104 x 115
Engine maximum 2000/25 EC power @ 2500 rpm (kW/hp)	43.5/59	50.7/69	58.8/80	65.5/89	72/98
Maximum torque at 1500 rpm (Nm)	219	272	298	352	370
TRANSMISSION					
Standard	12 Fwd / 4 Rev		12 Fwd / 12 Rev with mechanical shuttle		
Optional	12 Fwd / 12 Rev with mechanical shuttle		-	-	-
Optional with creeper	20 Fwd / 12 Rev with mechanical shuttle				
HYDRAULICS					
Lower link draft sensing	●	●	●	●	●
Rear linkage category	I-II	I-II	I-II	I-II	I-II
Mechanical lift with Fast Raise-Lower	●	●	●	●	●
Position, draft, mixed and float controls	●	●	●	●	●
Main pump flow – standard (l/min)	41	41	41	41	41
Main pump flow – Optional (l/min)	51.7○	51.7○	51.7○	51.7○	51.7○
Steering pump flow (l/min)	26.5	26.5	26.5	26.5	26.5
Maximum number of remote valves	3	3	3	3	3
Maximum lift capacity at ball ends with arms horizontal (kg)	3000	3000	3565	3565	3565
Continuous lift capacity through the range (610 mm behind ball ends) (kg)	2260	2260	2700	2700	2700
PTO					
540 rpm with Ground Speed PTO	●	●	●	●	●
540/540E or 540/1000 rpm with Ground Speed PTO	○	○	○	○	○
Engine speed at: 540 rpm (rpm)	2200	2200	2200	2200	2200
540economy rpm (rpm)	1715	1715	1715	1715	1715
1000rpm (rpm)	2380	2380	2380	2380	2380
PTO engagement	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
DIMENSIONS					
Overall length 2WD / 4WD (mm)	3791-3735	3791-3735	3921-3865	3921-3865	4004-3948
Wheelbase 2WD / 4WD (mm)	2118-2062	2118-2062	2248-2192	2248-2192	2331-2275
Total height ROPS (mm)	2428	2453	2483	2508	2558
Front track width 2WD / 4WD (mm)	1410-1910/1445-1875	1410-1910/1445-1875	1405-1905/1560-2000	1405-1905/1560-2000	1405-1905/1560-2000
Rear track width (mm)	1425-1925	1425-1925	1400-2000	1400-2000	1400-2000
Ground clearance, front axle lowest point 2WD / 4WD (mm)	495-340	525-365	525-390	555-415	575-465
WEIGHTS					
Total weight 2WD / 4WD without ballast (kg)	2320 / 2560	2320 / 2560	2650 / 3080	2650 / 3080	2820 / 3250
Maximum permissible restricted weights (kg)	5400	5400	5800	5900	6000

● Standard

○ Optional

- Not available



SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating Your Case IH Dealer

properly. Follow the product safety signs, and use any safety features provided.

This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment.

Visit our website: www.caseih.com or email: bosire.bogonko@tea.co.ke

TOYOTA TSUSHO EAST AFRICA LTD.

A TOYOTA Group Company

- Nairobi: +254-20-650 481 (Case Nairobi)
- Mombasa: +254-717-968 633 (Mombasa Toyota)
- Eldoret: +254-726-454 912 (Eldoret Toyota)
- Nakuru: +254-729-484 821 (Case Nakuru)
- Kericho: +254-52-21520/31120 (Kericho Toyota)
- Narok: +254-737-225 225 (Truck World)
- Tanzania: +255-783-302 061 (Toyota Tanzania)
- Uganda: +256-772-200 304 (Toyota Uganda)